



PRODUCT SPECIFICATIONS

Detail Photos

(on right from top to bottom)

Pre-assembled Az/EI Mount

Fine-elevation adjustment with stamped degree scale

RF tested Ku-Band feed assembly



1.2m RxTx Class II Antenna System

TYPE 123

Type approved for use on Intelsat and Eutelsat Satellite Systems



The Andrew Corporation Type 123 1.2m Class II RxTx Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain the critical parabolic shape necessary for transmit performance. The reflector optics feature a long focal length for excellent cross-pol performance, required by many satellite operators.

The Az/EI mount is constructed from heavy-gauge steel to provide a rigid support to the reflector. The Az/EI mount secures the antenna to any 2.88"-3.00" (73-76mm) O.D. mast and prevents slippage in high winds. A specially

formulated powder paint process offers excellent protection from weather-related corrosion.

- One-piece precision offset thermoset-molded reflector.
- Long focal length optics for low cross-pol performance.
- Fine azimuth and elevation adjustments.
- Galvanized .75" (19mm) O.D. side feed support legs and 2" (51mm) O.D. lower feed support.
- Plated hardware for maximum corrosion resistance.
- Available with Ku-Band Co-Pol. or Cross-Pol. Feeds.
- Class II system designed for typical 2W and 4W Ku-Band Block Up-Converters (BUCs)*

* 12 Lb. or 5.4 Kg. max. weight for RF electronics (BUC and LNB)

SPECIFICATIONS

TYPE 123 1.2m RxTx Class II Antenna System

Type Approval Information*

Antenna Model 62-12362-01

Intelsat Standard Standard G (IESS 601)

Approval Code IA077A00

Antenna Model 62-12362-01

Eutelsat Standard VSAT

Approval Code EA-V051

RF Performance

Effective Aperture	1.2m (48 in.)
Operating Frequency	Tx	13.75-14.50 GHz
	Rx	10.70-12.75 GHz
Polarization	Linear, Orthogonal
Gain (± 2 dBi)	Tx	43.3 dBi @ 14.25 GHz
	Rx	41.8 dBi @ 11.95 GHz
3 dB Beamwidth	Tx	1.2° @ 14.3 GHz
	Rx	1.5° @ 12.0 GHz
Sidelobe Envelope (Tx, Co-Pol dBi)	
1.5° < θ < 20°	29-25 Log θ
20° < θ < 26.3°	-3.5
26.3° < θ < 48°	32 - 25 Log θ
48° < θ < 180°	-10
Antenna Cross-Polarization	>30 dB in 1 dB Contour
Antenna Noise Temperature	10° El	45°K
	20° El	31°K
	30° El	24°K
VSWR	Tx	1.3:1
	Rx	1.5:1
Isolation, Port to Port	Tx	110 dB
	Rx	35 dB
Feed Interface	Tx	WR75 Cover Flange (UBR120)
	Rx	WR75 Cover Flange (UBR120)

(All specifications typical)

Mechanical Performance

Reflector Material	Glass Fiber Reinforced Polyester
Antenna Optics	One-Piece Offset Feed Prime Focus Long Focal Length
Mount Type	Elevation over Azimuth
Elevation Adjustment Range	7°-84° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous; $\pm 20^\circ$ Fine Adjustment
Mast Pipe Interface	2.88 in.-3.00 in. (73-76 mm) Diameter
Wind Loading	Operational	50 mi/h (80 km/h)
	Survival	125 mi/h (200 km/h)
Temperature	-50°C to 80°C
Humidity	0 to 100% (Condensing)
Atmosphere	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation	360 BTU/h/ft ²
Shock and Vibration	As Encountered During Shipping and Handling

*See our web site for a complete list of type approvals.



Andrew Corporation
10500 W. 153rd Street
Orland Park, IL 60462 USA

One Company. A World of Solutions.

Customer Support Center
From North America
Telephone: 1-800-255-1479
Fax: 1-800-349-5444
satcom@andrew.com

International
Telephone: +1-708-873-2307
Fax: +1-708-349-5444

Internet: www.andrew.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

Bulletin 11027 (2/05)

© 2005 Andrew Corporation, Orland Park, IL 60462 USA